

EB 250 - 900 WT Series (94500 - 373200 Btu/h) Packaged Compact Chillers

Model Number	Part Number RAL 7035 (Light Grey)	Voltage (V/Ph/Hz)	Capacity*			Nominal Current (A)	Tank Volume (gal)	Coolant Connections (NPT-F)	Width in (mm)	Depth in (mm)	Height in (mm)	Dry Weight lb (kg)
			(Btu/h)	(kW)	(Tons)							
EB 250 WT Indoor/Outdoor Rated (NEMA Type 12/4)	42532505320	460/3/60	94500	27.7	7.9	23.1	18.5	1	31 (787)	48 (1219)	56 (1422)	882 (400)
EB 300 WT Indoor/Outdoor Rated (NEMA Type 12/4)	42533005320	460/3/60	112000	32.8	9.3	28.1	31.7	1-1/2	31 (787)	66 (1676)	56 (1422)	926 (420)
EB 400 WT Indoor/Outdoor Rated (NEMA Type 12/4)	42534005320	460/3/60	151500	44.4	12.6	36.4	31.7	1-1/2	31 (787)	66 (1676)	56 (1422)	1323 (600)
EB 450 WT Indoor/Outdoor Rated (NEMA Type 12/4)	42534505320	460/3/60	190800	55.9	15.9	37	68	1-1/2	30 (762)	74 (1880)	57 (1448)	1446 (656)
EB 550 WT Indoor/Outdoor Rated (NEMA Type 12/4)	42535505320	460/3/60	218400	64.0	18.2	43	68	1-1/2	30 (762)	74 (1880)	57 (1448)	1482 (672)
EB 700 WT Indoor/Outdoor Rated (NEMA Type 12/4)	42537005320	460/3/60	294000	86.1	24.5	47	93	2	35 (889)	90 (2286)	82 (2083)	2273 (1031)
EB 900 WT Indoor/Outdoor Rated (NEMA Type 12/4)	42539005320	460/3/60	373200	109.3	31.1	63	93	2	35 (889)	90 (2286)	82 (2083)	2370 (1075)
Design	Rugged construction - (G90) galvanized steel with polyester powder coat finish											

* Water @ 64°F CWS / 90°F Ambient / 60Hz



For additional technical data, drawings and manuals.
www.pfannenbergusa.com



1 Ton = 12,000 Btu/h = 3517 Watts



EB 250 - 900 WT
Indoor / Outdoor Rated
(NEMA Type 12)

